



## Struktol Company of America

201 E. Steels Corners Road • P. O. Box 1649  
Stow, Ohio 44224-0649 • www.struktol.com  
Phone (330) 928-5188 • Fax (330) 928-8726

## TECHNICAL DATA

# STRUKTOL<sup>®</sup> MR 161A

*Mandrel Release Agent*

### COMPOSITION

Mixture of water-soluble polymers.

---

### **TYPICAL PROPERTIES**

---

Appearance	Amber, slightly cloudy liquid
Density at 20°C (kg/m <sup>3</sup> )	1100
Viscosity at 20°C (cP)	4800-5800
Pour point (°C)	0
Physiological Behavior	Refer to safety data sheet
Storage Stability	At least 2 years under normal storage conditions; protect from frost
Packaging	440 lb. drum

---

### RECOMMENDATIONS FOR APPLICATION

STRUKTOL<sup>®</sup> MR 161A is a multi-purpose mandrel release agent for ethylene acrylate rubber (e.g. vamac) and EPDM. It gives excellent release from peroxide cured EPDM.

STRUKTOL<sup>®</sup> MR 161A is biodegradable, miscible with water and can be easily rinsed away after application. It is also biologically degradable in waste-water treatment facilities.

### DOSAGE

*CONTACT A STRUKTOL TECHNICAL SALES REPRESENTATIVE FOR SPECIFIC RECOMMENDATIONS.*

(06/01/09)PAD/rca

The information herein is believed to be reliable, but is presented without guarantee or warranty, express or implied. Nothing contained herein is to be construed as a recommendation for any use which is in violation of an existing patent.