

# expect **MORE.** realize **MORE.**

INTELLIGENT ADDITIVE SOLUTIONS

**struktol**

Technical Service: 800-327-8649

Customer Service: 800-327-2709

Fax: 330-928-8726

## **STRUKTOL<sup>®</sup> TR 251** **PROCESSING AGENT**

### **COMPOSITION**

A complex oleochemical mixture containing mono and di amides and metal soap.

### **PROPERTIES**

Appearance	beige beads or pellets
Dropping Point (°C)	115-125
Specific Gravity	1.0
Physiological Behavior	refer to safety data sheet
Storage Stability	at least 2 years under normal storage conditions
Packaging	25 kg. PE bags

### **RECOMMENDATIONS FOR APPLICATION**

STRUKTOL<sup>®</sup> TR 251 is a unique blend of anionic and ionic surfactant with lubricant designed for applications where EBS (ethyl bis-stearamide) is commonly used. These include ABS compounds, rigid PVC extrusions, color concentrates and other high-filled applications (e.g. calcium carbonate filled polypropylene). STRUKTOL<sup>®</sup> TR 251 has enhanced functionality over EBS with similar gloss properties.

### **ADDITION LEVELS**

Levels between 1 - 2% are generally recommended in ABS, PVC and PS. Less than 0.5% is generally recommended for olefins.