



## Struktol Company of America

201 E. Steels Corners Road • P. O. Box 1649 • Stow, Ohio 44224-064  
Phone (330) 928-5188 • Fax (330) 928-0013  
www.struktol.com • customerservice@struktol.com

# TECHNICAL DATA

## **STRUKTOL<sup>®</sup> RP 06** *PROCESSING ADDITIVE*

### **COMPOSITION**

Proprietary blend of fatty acid derivatives.

<b><i>PROPERTIES</i></b>	<b><i>TYPICAL PROPERTIES</i></b>
Appearance	White to off-white pastille
Melting Point (°C)	50 - 60
Specific Gravity	1.08
Physiological Behavior	Refer to safety data sheet
Storage Stability	at least 2 years under normal storage conditions
Packaging	800 lb. Gaylord

### **RECOMMENDATIONS FOR APPLICATION**

STRUKTOL<sup>®</sup> RP 06 is designed to act as a processing aid and mold release used in polypropylene to modify viscosity. It has an engineered odor neutralizer added making it ideal for use in automotive applications.

STRUKTOL<sup>®</sup> RP 06 is also very useful in recycling applications.

### **DOSAGE**

0.1 – 2%

(01/21/2015)MSF/MTM/rca

The information herein is believed to be reliable, but is presented without guarantee or warranty, express or implied. Nothing contained herein is to be construed as a recommendation for any use which is in violation of an existing patent.