



Technical Data Sheet



Struktol Company of America, LLC 201 E. Steels Corners Road Stow, OH 44224-4921 (330) 928-5188 • (800) 327-8649 struktol.com • customerservice@struktol.com

STRUKTOL® WS 280 PASTE

Processing additive based on organosilicones

Composition

Condensation product of special fatty acid derivatives and silicones

Properties

Appearance Beige paste

Density $[kg/m^3]$ 1000

Acid value [mgKOH/g] Max. 5

Physiological behaviour Refer to safety data sheet

Storage stability At least 18 months under normal storage

conditions

Packaging 25 kg hobbocks







Recommendations for Application

STRUKTOL® WS 280 PASTE a processing additive based on organosilicones which in many applications shows superior performance compared to conventional products. It is highly compatible with rubber compounds. This enables utilisation of the highly efficient lubrication effects of silicone without exudation or bloom. Limited compatibility may occasionally be observed with compounds having a low filler content and/or a very high cross-link density.

In a unique way, STRUKTOL® WS 280 PASTE improves flow properties and release behaviour in the processing of rubber as well as mould release of vulcanisates.

STRUKTOL® WS 280 PASTE has an extremely low volatility at high temperatures and is particularly suitable for FPM compounds. It gives excellent release properties on mixing machinery, exceptionally good flow properties, and reduces mould fouling. STRUKTOL® WS 280 PASTE gives not only better extrusion properties, but is excellent also for injection moulding.

Dosage

0.5 - 1.5 phr

It should be noted that, compared to usual processing additives, the same results can be achieved with lower dosages.







Disclaimer:

This publication is not a specification and does not contain any instruction manual or operating guidelines. It is provided for information purposes only and without any responsibility. Schill + Seilacher "Struktol" makes no representations about the accuracy, reliability or completeness of the information in this publication. We reserve the right to revise our not specified products and the information at any time without notice. The information in this publication is based on the present state of our knowledge and experience and serves the general description of our products and their possible applications. Our technical advice and recommendations, whether verbal, in writing or by way of trials, do not absolve the recipient, on account of the many outside influences which may affect the product use and application, from their own testing and trials. A legally binding assurance based on the information contained herein regarding particular properties or the suitability for definite customer applications cannot be derived from our information.

In accordance with the provisions of our General Terms and Conditions of Sale and Delivery, which can be accessed under www.struktol.de. Schill+Seilacher "Struktol" excludes liability for slightly negligent breaches of obligations arising from the use of the information contained in this publication, provided that they do not relate to damage from injury to life, limb or health or guarantees or claims under the Product Liability Act are affected. Furthermore, the liability for the breach of obligations, the fulfilment of which is essential for the proper execution of the contract and on the observance of which the customer may regularly rely, remains unaffected. The same applies to breaches of duty by our agents.

This technical datasheet is created automatically and is valid without signature.

